

CP-Q2

80mm Width w/Auto-Cutter

RS232 + USB

Great and Affordable 80mm Thermal Printer for Every Applications



1. Compact

It is cool and fashioned design. CP-Q2 is with compact and ergonomically designed to maximise valuable counter space. With a small footprint and comfortable chassis, CP-Q2 is a good printer for retail and hospitality market.



2. Functional and Reliable

- 203 dpi resolutions
- With print speed of 200mm/second
- Built-in AOI printer head and high function Auto-cutter with MTBF 1-1.5 million cuts
- Easy paper loading
- RS232 + USB interface both(optional for LAN)



3. Cost-effective and Affordable

Exceptionally durable and strong-features, CP-Q2 is a affordable printer for retailers and hospitality business to save their budget to own.

Ordering information :

CP-Q2BU: 80mm thermal receipt printer, 200mm speed, RS232 + USB, Black.

CP-Q2BN: 80mm thermal receipt printer, 200mm speed, LAN



Technical Specifications

Model Numbers CP-Q2

Printing	
Printing method	Direct thermal
Print width	72mm
Column capacity	576 dots/line 512 dots/line
Printing speed	200mm/s
Interface	USB+Serial , LAN
Printing paper	79.5±0.5mm×φ80mm
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese,traditional Chinese - 21 columns or 24 columns
Character size	ANK , Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)
Cutter	
Auto cutter	Partial
Barcode Character	
Code Page	PC347 (Standard Europe) 、 Katakana 、 PC850 (Multilingual) 、 PC860 (Portuguese) 、 PC863 (Canadian-French) 、 PC865 (Nordic) 、 West Europe 、 Greek 、 Hebrew 、 East Europe 、 Iran 、 WPC1252 、 PC866 (Cyrillic#2) 、 PC852 (Latin2) 、 PC858 、 IranII 、 Latvian 、 Arabic 、 PT151 (1251)
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/C ODE128

Buffer	
Input buffer	64 K Bytes
NV Flash	256k bytes
Power	
Power adaptor	Input : AC 110V/220V, 50~60Hz
Power source	Output : DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	1.0KG
Dimensions	183.×140×141.5mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60°C) humidity(10~80%)
Reliability MAX	
Cutter life	1-1.5 million cuts
Printer head life	50KM



BIRCH[®]
BIRCH TECHNOLOGY INC

Birch is a trademark of Birch Technology
All other products, brands or companies are trademarks or registered trademarks of their respective companies.
Specifications are subject to change without prior notice

Contact us for details