



Mobile Label Printer

DBL 441B




- LCD screen, easy to operate
- Low noise, high quality, high speed printing
- 2550mAh large capacity battery, long standby
- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS emulation compatible



DBL 441B

Mobile Label Printer



Printing	DBL 441B
Resolution	203 DPI
Printing method	Direct Thermal
Max.print speed	100 mm (4") / s
Max.print width	104 mm(4.09")
Max.print length	1016 mm (40")

Media	
Media type	Continuous, gap, black mark
Media width	40 mm ~ 112 mm
Media thickness	0.06 mm ~0.16 mm
Paper roll diameter	50 mm

Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM
Interface	USB+Bluetooth Optional:USB+WIFI / NFC
Screen	1.3"OLED
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor

Performance Features	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST
2D bar code	PDF-417, Maxicode, DataMatrix, QR code, MPDF417, AZTEC, MAXICODE
Rotation	0°、 90°、 180°、 270°
Emulaion	TSPL、 EPL、 ZPL、 DPL、 CPCL、 ESC/POS

Physical Features	
Dimensions	150 mm (L) x 131 mm (W) x 64 mm (H)
Weight	550g

Reliability	
Printer head life	30Km

Software	
Operation system	Windwos / Linux / Mac / Android / iOS
SDK	Windows / Android / iOS

Power supply	
Power input	DC 5V / 2A
Battery	7.2V/2550mAh

Options	
Optional accessories	①Shoulder strap ②Protection bag ③Dual-slot battery charger

Environmental Conditions	
Operation environment	5~ 40°C(41~104°F), Humidity: 25 ~ 85% no condensing
Storage environment	-40 ~ 60°C(-40~140°F), Humidity: 10 ~ 90% no condensing



www.dbautomation.lk

